

# TANKBLANKET™

The TankBlanket system is easy to retro-fit, operate & maintain.

Installed correctly, that is, in line with our installation guidelines and not abused, then normal wear and tear will see TankBlanket serve you for many years.

TankBlankets have been in use in the USA since 1991 and Motorhomes are still in use today with their original TankBlankets in operation!

To ensure TankBlanket does not let you down please understand and follow these guidelines.

1. Make sure you only use TankBlanket when there is liquid in the fresh water or waste tank.
2. Turn 'ON' TankBlanket when you know the ambient temperature will approach freezing. The LED illuminated switch will indicate there is power to the circuit.
3. When the contents of the fresh or waste tank drops to 6.7 °C the thermostat on TankBlanket will turn the heater element 'ON'.
4. When the temperature in the fresh or waste tank rises to 18 °C the TankBlankets thermostat will turn the system 'OFF'.
5. Turn the TankBlanket power switch 'OFF' when draining fluid, hooking up or starting a power generator. This will prevent any damage to the built-in TankBlanket thermostat.
6. Turn 'OFF' the TankBlanket power switch when the ambient temperature is above freezing.
7. Periodically, do a visual check of your TankBlanket system to ensure cables, connections and TankBlanket pads are as installed and have not been damaged or become unconnected.

**Note:** To preserve your habitation battery charge, where available, use TankBlanket inconjunction with a 240V hook up.

**Note:** The TankBlanket system is modular in design and can be upgraded at anytime resulting in the ultimate winterisation system!

-----//-----